

# SmartSource<sup>®</sup>

Professional Elite Series Your Remote Deposit Capture Solution



SmartSource Merchant Elite



SmartSource Elite 55 with Endorser

# SmartSource Elite Series Scanners

Digital Check, the recognized world leader for paymentrelated products and services, offers the SmartSource Elite series, compact-size scanners optimized for remote deposit capture solutions. Like all scanners in the Digital Check portfolio, the SmartSource Elite series provides industry-leading quality and performance.

The SmartSource Elite series scanners are designed with the remote deposit capture operator in mind. The robust, maintenance-free design and ease of use ensure a positive experience for the remote deposit capture operator.

#### SmartSource Merchant Elite – Ideal for Remote Deposit Capture

The SmartSource Merchant Elite scanner has been optimized for remote deposit capture applications. With a processing speed of 55 documents per minute and a 100-document auto-feeder the SmartSource Merchant Elite scanner quickly processes batches of documents.

# SmartSource Elite 55 for Applications Requiring Endorsing

The SmartSource Elite 55 scanner is configured with a highly flexible rear ink-jet endorser for remote deposit capture applications where endorsing the check is required.

## **ID Card Scanning**

The SmartSource Elite series scanners have the capability to scan rigid items such as ID and health insurance cards, eliminating the need for additional document scanning hardware.



### SmartSource Elite Series Technical Information

| Document Processing Throughput   | Single Output Pocket  |
|--|---|
| 55 documents per minute  | 150 item pocket capacity  |
| Power Requirements   | Automatic Document Feeder   |
| 100-240 VAC @ 50/60 Hz<br>Operating Power: 20 W<br>Standby Power: 3 W  | Up to 100 item hopper capacity<br>Automatically opens for ease of use (Elite 55 only)<br>Double document detection  |
| Weight   | Dimensions  |
| Installed weight: 4.7 lbs (2.1 kg)<br>Power supply: 0.55 lbs (0.25 kg)   | Length: 8.86 in (22.5 cm) Depth: 5.39 in (13.7 cm)<br>Height: 6.99 in (17.8 cm)   |
| Certifications   | Magnetic Ink Character Recognition (MICR)   |
| CE, UL/TUV, CSA, RoHS, VCCI, FCC Class A   | E13B and CMC7 read with auto-detect   |
| 2010 Appliance Efficiency Regulations, California, Title 20  | Image Capture   |
| Document SizesDocument size- Height: 2.00 to 6.00 inches (5.08 to 15.24 cm)- Imaged height: 4.25 inches (10.80 cm)- Length: 2.90 to 9.25 inches (7.37 to 23.5 cm)(Adding Machine Tape Mode supports up to 6 feet)Document weight- Paper weight: 16 to 28 lb (60 to 105 gsm)- Accepts 12 lb (45 gsm) paper at a reduced throughput and pocket capacity- Alternate input accepts ID cards and other media up to 0.030 inches thick | Front and rear image capture at 300 dots per inch (dpi)<br>Up to five (5) bi-tonal and grayscale images<br>Image renditions available<br>- Bi-tonal (black/white)<br>- Gray level (256 gray shades)<br>Image resolutions available<br>- 240, 200 dpi, gray level or bi-tonal<br>- 120, 100 dpi, gray level<br>Image Compression Standards<br>CCITT Group 4 (bi-tonal images)<br>JPEG Baseline (gray level images) |
| Communication Interface  |   |
| USB 2.0 high-speed   | Operator Interface  |
| Operating Systems<br>Windows XP Professional 32-bit  | Combined power switch, feeder start/stop and SmartClear button<br>Light Emitting Diode (LED)  |
| Windows VISTA Business 32 and 64-bit   | Optical Character Recognition (OCR)   |
| Windows 7 Professional 32 and 64-bit<br>Windows 8 Professional 32 and 64-bit<br>Windows 10 Professional 32 and 64-bit  | OCR-A, OCR-B, E13B, and barcode fonts supported<br>Two (2) 0.50 inch OCR scan bands provided<br>96 characters per scan band   |
| Rear Endorsement (Elite 55 Only)   | MICR/OCR combine read   |
| Ink jet print cartridge (600 dpi)<br>One (1) to four (4) line endorsement, any True Type font<br>Graphics capable for logos and signatures<br>Three (3) levels of print quality (economy, standard, or premium)  |   |
| Application Programming Interfaces (API)<br>CAPI (Common Application Programming Interface)  |   |

NOTES: Not every API Operating System combination may be qualified. Contact your application provider for more information.

Specific capabilities may not be supported by every API or will require a Minimum API version. Contact Digital Check for more information.

SmartSource and ReceiptNOW are<br/>registered trademarksregistered trademarksofDigital Check Corp.Rangerisaregistered trademarkofSilverBulletTechnology,Inc.Allotherbrandsandproductsreferencedinthis document areacknowledgedtobethetrademarksorregisteredtrademarksoftheirrespectiveholders.Specificationsaresubjecttochangewithoutnotice.

3/17 All rights reserved. © 2017 Digital Check Corp.



Device Suite

Twain

Ranger<sup>®</sup> for SmartSource



•

.

.

•

.

•

**SmartTIP** For more information use your smartphone and snap a photo.